


PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines



Model	MicroFlow Touch	MiniFlow Rapid	PowerFlow	MultiFlow
Typical Usage	Inside	In/Outside	Outside	Outside
Fiber/Cable Diameter	0.8-5.0 mm	4-12 mm	8-25 mm	8-32 mm
Tube Size (OD)	5-16 mm	7-20 mm	18-70 mm	18-70 mm
Part #	101-10051	101-10031	101-10001	101-10002
Install Speed to	90 m/min.	100 m/min.	80 m/min.	80 m/min.
Distance	Up to 2.5 km	Up to 3.5 km	Up to 10 km*	Up to 10 km*
Recommended Airflow Recommended Pressure	200-500 l/pr. min. 8-16 bar air	1,000 l/pr. min. 8-16 bar air	8,000-12,000 l/pr. min. 8-12 bar air	8,000-12,000 l/pr. min. 8-12 bar air
Length: Width: Height: Weight:	Machine: 25 cm Control Box: 20 cm 15 cm 15 cm 22 cm 8 cm 9.7 kg 1.9 kg	650 mm 225 mm 210 mm 24 kg	650 mm 230 mm 350 mm 38 kg	700 mm 230 mm 350 mm 40 kg
Unique Features	Automatic Buckle Detection Adjustable Torque Preset Automatic Stop Adjustable Speed Control Speed, Torque & Count Display Air Pressure & Flow Regulation Easy to Operate Simple Maintenance	Use with Air or Water Push Force Monitor Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance	Use with Air or Water* Installs Single Cable Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance	Use with Air or Water* Jets Tubes or Cable Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance



For further information please contact:

